

VGA/Audio Wall Plate

Single-gang, Decora® compatible plate to connect computer & audio to a TV or ceiling mounted projector and amplifier.

WALL PLATE SPECIFICATIONS

Display Input	VGA (UXGA, 1600x1200)
Audio Input	3.5mm, stereo
Output	7in lead, VGA + 3.5mm to 13 pin DIN
Certifications	UL listed, RoHS compliant

CABLE SPECIFICATIONS

Composition	ø13mm/0.5in, plenum rated PVC
Length	15.25m/50ft
Connectors	13 pin DIN to VGA + 3.5mm



VGA/Audio/RCA Wall Plate

Single-gang, Decora® compatible plate to connect computer & audio and video device to a TV or ceiling mounted projector and amplifier.

WALL PLATE SPECIFICATIONS

Display Input	VGA (UXGA, 1600x1200)
Audio Inputs	3.5mm, stereo, RCA stereo
Video Inputs	VGA, Composite Video
Output	7in lead, VGA + 3.5mm + RCA video/stereo audio to 13 pin DIN
Certifications	UL listed, RoHS compliant

CABLE SPECIFICATIONS

Composition	ø13mm/0.5in, plenum rated PVC
Length	15.25m/50ft
Connectors	13 pin DIN to VGA + 3.5mm + RCA video/stereo



VGA/Audio/USB Wall Plate

Single-gang, Decora® compatible plate to connect computer & audio and network device to a TV or ceiling mounted projector and amplifier.

WALL PLATE SPECIFICATIONS

Display Input	VGA (UXGA, 1600x1200)
Audio Input	3.5mm, stereo
Input	USB-B pass through
Output	7in lead, VGA + 3.5mm to 13 pin DIN and USB-A
Certifications	UL listed, RoHS compliant

VGA + AUDIO CABLE SPECIFICATIONS

Composition	ø13mm/0.5in, plenum rated PVC
Length	15.25m/50ft
Connectors	13 pin DIN to VGA + 3.5mm



HDMI Pass-Through Wall Plate

Single-gang, Decora® compatible plate to connect computers, tablets, document cameras and more to drive HDMI projectors and digital displays.

WALL PLATE SPECIFICATIONS

Wall plate	Decora®-compatible single-gang
HDMI	1.4 Compliant
Video resolutions	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
PC resolution	Up to 1600x1200 UXGA
Audio support	Digital 2.0CH/5.1CH LPCM, Dolby Digital, or DTS
Output	6in lead, Type A female
Input	Type A female connector
EDID Emulator	HDMI 2K



HDMI OPTICAL CABLE SPECIFICATIONS

Composition	ø3mm/0.13in, plenum + LSZH plenum-rated PVC
HDMI	1.4, 1.4a, 1.4b, 2.0 compliant
Video resolutions	Up to 4K2K @ 60Hz, 4:4:4
Video bandwidth	18Gbps max with HDMI 2.0
HDCP	2.2, EDID, CEC, DDC, HPD compliant
Length	20m/65ft or 40m/131ft
Connectors	HDMI-D to HDMI-D with two HDMI-A adaptors

Audio Out Wall Plate

Single-gang audio out wall plate for use with ezRoom and FrontRow Control lesson capture software. Connect the line output of the ezRoom system to the mic input on the computer to capture voice and audio.

WALL PLATE SPECIFICATIONS

Input	3.5mm, mono
Output	RJ45
Certifications	UL listed, RoHS compliant

CABLE SPECIFICATIONS

Composition	Plenum-rated Cat5
Length	15m/50ft



Audio/USB Wall Plate

Single-gang wall plate with audio pass through to connect computers, tablets, Blu-Ray players and more to drive projectors and digital displays.

WALL PLATE SPECIFICATIONS

Audio Input	3.5mm, stereo
USB Input	USB-B
Audio Output	3.5mm, stereo
USB Output	7in lead, USB-A
Certifications	UL listed, RoHS compliant

USB CABLE SPECIFICATIONS

Composition	ø5mm/0.20in, plenum-rated PVC Built-in active repeaters
Length	15.25m/50ft
Connectors	USB-A to USB-B



Learn more at gofrontrow.com